

Tapered roller bearing 32248-JTEKT - 32248-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/32248-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾			
d	D	T	B	C	C _r	C _{0r}	C ₉₀	C ₁₀₀	Grease lub.	Oil lub.				
240	440	127	120	100	5	4	1 530	2 480	740	980	32248			
Dimension series to ISO 955 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)												
		d _{1a} min.	d _{1a} max.	d _{2a} min.	d _{2a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.	r _{1a} min.	r _{1a} max.	Constant e	Axial load factors Y ₁	Axial load factors Y ₀
—	106.1	262	282	422	365	415	16	14	4	3	0.43	1.39	0.77	76.4

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952421735
Inside diameter	240 mm
Outside diameter	440 mm
Thickness	127 mm
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE