

Tapered roller bearing 32052-JR-JTEKT - 32052-JR-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/32052-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾				
d	D	T	B	C	C _r	C _{0r}	Grease lub.	Oil lub.						
260	400	87	87	65	1170	2170	770	1000	32052JR					
Dimension series to ISO355 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d _{1a} min.	d _{1a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.	r _{1a} min.	r _{1a} max.		Y ₁	Y ₀		
4FC	85.0	282	287	382	352	383	14	22	4	3	0.43	1.38	0.76	39.5

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250232589
Inside diameter	260 mm
Inside diameter	10.236" inch
Outside diameter	400 mm
Outside diameter	15.748" inch
Thickness	87 mm
Thickness	3.425" inch
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE