

Tapered roller bearing 32252-JTEKT - 32252-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/32252-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾			
d	D	T	B	C	C _r	C _{0r}	C ₉₀	C ₁₀₀	Grease lub.	Oil lub.				
260	480	137	130	106	6	5	1 760	2 870	660	880	32252			
Dimension series to ISO 955 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)												
		d _{1a} min.	d _{1a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.	r _{1a} min.	r _{1a} max.	Constant e	Axial load factors Y ₁	Axial load factors Y ₀	(Refer. 1) Mass (kg)	
—	115.2	288	300	458	400	455	16	30	5	4	0.43	1.39	0.77	102

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952421797
Inside diameter	260 mm
Outside diameter	480 mm
Thickness	137 mm
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE