

## Tapered roller bearing 17098-17244-JTEKT - 17098-17244-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/17098-17244-jtekt>

Single-row tapered roller bearings  
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	
d	D	T	B	C	r <sub>1</sub> max.	r <sub>1</sub> min.	C <sub>r</sub>	C <sub>10</sub>	Grease lub.	Oil lub.
24.981	62.000	16.002	16.566	14.288	1.6	1.6	38.0	40.6	6 700	8 900

  

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Con-stant	Axial load factors		(Refer) Mass (kg)	
Inner ring	Outer ring	a	d <sub>a</sub>	d <sub>b</sub>	D <sub>a</sub>	D <sub>b</sub>	r <sub>a</sub> max.	r <sub>b</sub> max.	e	Y <sub>1</sub>	Y <sub>2</sub>	Inner ring	Outer ring
17098	17244	12.7	33.0	30.5	54.0	57.0	1.6	1.6	0.38	1.57	0.86	0.162	0.090

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952425597
Inside diameter	24.981 mm
Inside diameter	0.984" inch
Outside diameter	62 mm
Outside diameter	2.441" inch
Thickness	16.002 mm
Thickness	0.63" inch
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE