


Tapered roller bearing 15101-15243-JTEKT - 15101-15243-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/15101-15243-jtekt>

Single-row tapered roller bearings
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r</i> _a	<i>r</i> _b	<i>C</i> _r	<i>C</i> ₁₀	Grease lub.	Oil lub.
25.400	61.912	19.050	20.638	14.288	0.8	2.0	44.6	50.7	6 400	8 600

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer.) Mass (kg)	
Inner ring	Outer ring	<i>a</i>	<i>d</i> _a	<i>d</i> _b	<i>D</i> _a	<i>D</i> _b	<i>r</i> _a max.	<i>r</i> _b max.	<i>e</i>	<i>Y</i> ₁	<i>Y</i> ₂	Inner ring	Outer ring
15101	15243	13.2	32.5	31.5	55.0	58.0	0.8	2.0	0.35	1.71	0.94	0.215	0.080

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952425665
Inside diameter	25.4 mm
Inside diameter	1" inch
Outside diameter	61.912 mm
Outside diameter	2 7/16" inch
Thickness	19.05 mm
Thickness	3/4" inch
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE