

# Tapered roller bearing 15101-15250R-JTEKT - 15101-15250R-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/15101-15250r-jtekt>

Single-row tapered roller bearings  
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	
$d$	$D$	$T$	$B$	$C$	$r_a$ max.	$r_b$ max.	$C_r$	$C_{10}$	Grease lub.	Oil lub.
25.400	63.500	19.050	20.638	14.288	0.8	1.2	44.6	50.7	6 400	8 600

  

Bearing No.		Load center (mm)	Mounting dimensions (mm)					Constant	Axial load factors		(Refer) Mass (kg)		
Inner ring	Outer ring	$a$	$d_a$	$d_b$	$D_a$	$D_b$	$r_a$ max.	$r_b$ max.	$e$	$Y_1$	$Y_2$	Inner ring	Outer ring
15101	15250R	13.2	32.5	31.5	55.0	59.0	0.8	1.2	0.35	1.71	0.94	0.215	0.097

## PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952425672
Inside diameter	25.4 mm
Inside diameter	1" inch
Outside diameter	63.5 mm
Outside diameter	2 1/2" inch
Thickness	19.05 mm
Thickness	3/4" inch
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE