

## Tapered roller bearing 2687-2631-JTEKT - 2687-2631-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/2687-2631-jtekt>

Single-row tapered roller bearings  
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	
$d$	$D$	$T$	$B$	$C$	$r_1$ max.	$r_1$ min.	$C_r$	$C_{10}$	Grease lub.	Oil lub.
25.400	66.421	23.812	25.433	19.050	1.2	1.2	67.0	75.2	6 500	8 700

  

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer to)	
Inner ring	Outer ring	$a$	$d_a$	$d_b$	$D_a$	$D_b$	$r_a$ max.	$r_b$ max.	$e$	$Y_1$	$Y_2$	Inner ring	Outer ring
2687	2631	13.9	33.5	31.5	58.0	60.0	1.2	1.2	0.25	2.36	1.30	0.272	0.163

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952425702
Inside diameter	25.4 mm
Outside diameter	66.421 mm
Thickness	23.812 mm
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE