

## Tapered roller bearing 02473-02420-JTEKT - 02473-02420-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/02473-02420-jtekt>

Single-row tapered roller bearings  
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	
d	D	T	B	C	r <sub>1</sub> max.	r <sub>1</sub> min.	C <sub>r</sub>	C <sub>10</sub>	Grease lub.	Oil lub.
25.400	68.262	22.225	22.225	17.462	0.8	1.6	51.0	61.1	6 000	8 000

  

Bearing No.		Load center (mm)	Mounting dimensions (mm)					Constant	Axial load factors		(Refer to Mass (kg))		
Inner ring	Outer ring	a	d <sub>a</sub>	d <sub>b</sub>	D <sub>a</sub>	D <sub>b</sub>	r <sub>a</sub> max.	r <sub>b</sub> max.	e	Y <sub>1</sub>	Y <sub>2</sub>	Inner ring	Outer ring
02473	02420	17.1	34.5	33.5	59.0	63.0	0.8	1.6	0.42	1.44	0.79	0.275	0.150

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952425719
Inside diameter	25.4 mm
Outside diameter	68.262 mm
Thickness	22.225 mm
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE