

Tapered roller bearing 15580-15523-JTEKT - 15580-15523-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/15580-15523-jtekt>

Single-row tapered roller bearings inch series **Koyo**



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r</i> ₁ max.	<i>r</i> ₁ min.	<i>C</i> _r	<i>C</i> _{10v}	Grease lub.	Oil lub.
26.988	60.325	19.842	17.462	15.875	3.6	1.6	37.8	42.7	7 000	9 400

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer to)	
Inner ring	Outer ring	<i>a</i>	<i>d</i> _a	<i>d</i> _b	<i>D</i> _a	<i>D</i> _b	<i>r</i> _a max.	<i>r</i> _b max.	<i>e</i>	<i>Y</i> ₁	<i>Y</i> ₂	Inner ring	Outer ring
15580	15523	15.1	38.5	32.0	51.0	54.0	3.6	1.6	0.35	1.73	0.95	0.140	0.122

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952425825
Inside diameter	26.988 mm
Outside diameter	60.325 mm
Thickness	19.842 mm
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE