

Tapered roller bearing 41126-41286-JTEKT - 41126-41286-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/41126-41286-jtekt>

Single-row tapered roller bearings inch series Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
d	D	T	B	C	r ₁ max.	r ₁ min.	C _r	C ₁₀	Grease lub.	Oil lub.
28.575	72.626	24.608	24.267	17.462	1.6	1.6	61.8	60.5	6 100	8 100

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer to)	
Inner ring	Outer ring	a	d _a	d _b	D _a	D _b	r _a max.	r _b max.	e	Y ₁	Y ₂	Inner ring	Outer ring
41126	41286	20.7	41.5	36.5	61.0	68.0	1.6	1.6	0.80	1.00	0.55	0.295	0.177

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952425900
Inside diameter	28.575 mm
Outside diameter	72.626 mm
Thickness	24.608 mm
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE