


Tapered roller bearing 17118-17244-JTEKT - 17118-17244-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/17118-17244-jtekt>

Single-row tapered roller bearings ————— **Koyo**
inch series



| Boundary dimensions (mm) | | | | | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | |
|--------------------------|----------|----------|----------|----------|----------------------|----------------------|-------------------------|-----------------------|--------------------------------------|----------|
| <i>d</i> | <i>D</i> | <i>T</i> | <i>B</i> | <i>C</i> | <i>r_a</i> | <i>r_b</i> | <i>C_r</i> | <i>C_{0r}</i> | Grease lub. | Oil lub. |
| 29.987 | 62.000 | 16.002 | 16.566 | 14.288 | 1.6 | 1.6 | 38.0 | 40.6 | 6 700 | 8 900 |

| Bearing No. | | Load center (mm) | Mounting dimensions (mm) | | | | | | Constant | Axial load factors | | (Refer to) | |
|-------------|------------|------------------|--------------------------|----------------------|----------------------|----------------------|---------------------------|---------------------------|----------|----------------------|----------------------|------------|------------|
| Inner ring | Outer ring | <i>a</i> | <i>d_a</i> | <i>d_b</i> | <i>D_a</i> | <i>D_b</i> | <i>r_a</i> max. | <i>r_b</i> max. | <i>e</i> | <i>Y₁</i> | <i>Y₂</i> | Inner ring | Outer ring |
| 17118 | 17244 | 12.7 | 37.0 | 34.5 | 54.0 | 57.0 | 1.6 | 1.6 | 0.38 | 1.57 | 0.86 | 0.135 | 0.090 |

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | JTEKT |
| N° Ean13 | 3663952425955 |
| Inside diameter | 29.987 mm |
| Outside diameter | 62 mm |
| Thickness | 16.002 mm |
| Packaging | 1 |

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE