


Tapered roller bearing 02476-02420-JTEKT - 02476-02420-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/02476-02420-jtekt>

Single-row tapered roller bearings inch series Koyo



Boundary dimensions (mm)								Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r</i> _a	<i>r</i> _b	<i>r</i> _s	<i>C</i> _r	<i>C</i> ₁₀	Grease lub.	Oil lub.
31.750	68.262	22.225	22.225	17.462	0.8	1.6		51.0	61.1	6 000	8 000

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer to)	
Inner ring	Outer ring	<i>a</i>	<i>d</i> _a	<i>d</i> _b	<i>D</i> _a	<i>D</i> _b	<i>r</i> _a max.	<i>r</i> _b max.	<i>e</i>	<i>Y</i> ₁	<i>Y</i> ₂	Inner ring	Outer ring
02476	02420	17.1	39.0	38.5	59.0	63.0	0.8	1.6	0.42	1.44	0.79	0.226	0.150

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952426075
Inside diameter	31.75 mm
Outside diameter	68.262 mm
Thickness	22.225 mm
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE