

Tapered roller bearing 16137-16284-JTEKT - 16137-16284-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/16137-16284-jtekt>

Single-row tapered roller bearings
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
d	D	T	B	C	r_1 max.	r_1 min.	C_r	C_{10}	Grease lub.	Oil lub.
34.925	72.238	20.638	20.638	19.875	3.6	1.2	49.7	61.3	5 600	7 400

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer to) Mass (kg)	
Inner ring	Outer ring	a	d_a	d_b	D_a	D_b	r_a max.	r_b max.	e	Y_1	Y_2	Inner ring	Outer ring
16137	16284	16.6	46.5	40.5	63.0	67.0	3.6	1.2	0.40	1.49	0.82	0.236	0.144

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952426310
Inside diameter	34.925 mm
Outside diameter	72.238 mm
Thickness	20.638 mm
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE