

## Tapered roller bearing 16137-16284-JTEKT - 16137-16284-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/16137-16284-jtekt>

Single-row tapered roller bearings  
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	
d	D	T	B	C	r <sub>1</sub> max.	r <sub>1</sub> min.	C <sub>r</sub>	C <sub>10</sub>	Grease lub.	Oil lub.
34.925	72.238	20.638	20.638	19.875	3.6	1.2	49.7	61.3	5 600	7 400

  

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer to)	
Inner ring	Outer ring	a	d <sub>a</sub>	d <sub>b</sub>	D <sub>a</sub>	D <sub>b</sub>	r <sub>a</sub> max.	r <sub>b</sub> max.	e	Y <sub>1</sub>	Y <sub>2</sub>	Inner ring	Outer ring
16137	16284	16.6	46.5	40.5	63.0	67.0	3.6	1.2	0.40	1.49	0.82	0.236	0.144

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952426310
Inside diameter	34.925 mm
Outside diameter	72.238 mm
Thickness	20.638 mm
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE