

## Tapered roller bearing 02877-02820-JTEKT - 02877-02820-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/02877-02820-jtekt>

Single-row tapered roller bearings  
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	
d	D	T	B	C	r <sub>1</sub> max.	r <sub>1</sub> min.	C <sub>r</sub>	C <sub>10</sub>	Grease lub.	Oil lub.
34.925	73.025	22.225	22.225	17.462	3.6	3.2	55.0	65.7	5 500	7 400

  

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer to Mass (kg))	
Inner ring	Outer ring	a	d <sub>a</sub>	d <sub>b</sub>	D <sub>a</sub>	D <sub>b</sub>	r <sub>a</sub> max.	r <sub>b</sub> max.	e	Y <sub>1</sub>	Y <sub>2</sub>	Inner ring	Outer ring
02877	02820	18.4	48.5	42.0	62.0	68.0	3.6	3.2	0.45	1.32	0.73	0.262	0.158

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952426327
Inside diameter	34.925 mm
Outside diameter	43.025 mm
Thickness	22.225 mm
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE