

Tapered roller bearing 339-332-JTEKT - 339-332-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/339-332-jtekt>

Single-row tapered roller bearings
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
d	D	T	B	C	r_1 max.	r_1 min.	C_r	C_{10}	Grease lub.	Oil lub.
35.000	80.000	21.000	22.400	17.826	0.8	1.2	68.0	74.8	4 900	6 600

Bearing No.		Load center (mm)	Mounting dimensions (mm)					Constant	Axial load factors		(Refer to) Mass (kg)		
Inner ring	Outer ring	a	d_a	d_b	D_a	D_b	r_a max.	r_b max.	e	Y_1	Y_2	Inner ring	Outer ring
339	332	15.1	42.5	41.5	73.0	75.0	0.8	1.2	0.27	2.20	1.21	0.385	0.144

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952426433
Inside diameter	35 mm
Outside diameter	80 mm
Thickness	21 mm
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE