

Tapered roller bearing 25880R-25821-JTEKT - 25880R-25821-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/25880r-25821-jtekt>

Single-row tapered roller bearings
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
d	D	T	B	C	r ₁ max.	r ₁ min.	C _r	C ₁₀	Grease lub.	Oil lub.
36.487	73.025	23.812	24.608	19.050	1.6	0.8	72.2	87.3	5 600	7 400

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer to Mass (kg))	
Inner ring	Outer ring	a	d _a	d _b	D _a	D _b	r _a max.	r _b max.	e	Y ₁	Y ₂	Inner ring	Outer ring
25880R	25821	15.8	44.0	42.0	65.0	68.0	1.6	0.8	0.29	2.07	1.14	0.294	0.165

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952426440
Inside diameter	36.487 mm
Outside diameter	73.025 mm
Thickness	23.812 mm
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE