

## Tapered roller bearing 19150R-19283-JTEKT - 19150R-19283-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/19150r-19283-jtekt>

Single-row tapered roller bearings inch series **Koyo**



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	
d	D	T	B	C	r <sub>1</sub> max.	r <sub>1</sub> min.	C <sub>r</sub>	C <sub>10</sub>	Grease lub.	Oil lub.
38.100	71.996	17.018	16.520	14.288	1.6	1.6	46.1	53.8	5 700	7 600

  

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer to Mass (kg))	
Inner ring	Outer ring	a	d <sub>a</sub>	d <sub>b</sub>	D <sub>a</sub>	D <sub>b</sub>	r <sub>a</sub> max.	r <sub>b</sub> max.	e	Y <sub>1</sub>	Y <sub>2</sub>	Inner ring	Outer ring
19150R	19283	15.7	45.0	43.0	63.0	66.0	1.6	1.6	0.44	1.35	0.74	0.167	0.132

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952426587
Inside diameter	38.1 mm
Outside diameter	71.996 mm
Thickness	17.018 mm
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE