

Tapered roller bearing 16150-16283-JTEKT - 16150-16283-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/16150-16283-jtekt>

Single-row tapered roller bearings ————— **Koyo**
inch series



Boundary dimensions (mm)								Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r</i> ₁ max.	<i>r</i> ₂ min.	<i>C</i> _r	<i>C</i> _{10v}	Grease lub.	Oil lub.	
38.100	72.238	23.812	20.638	19.050	3.6	2.4	49.7	61.3	5 600	7 400	

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer to)	
Inner ring	Outer ring	<i>a</i>	<i>d</i> _a	<i>d</i> _b	<i>D</i> _a	<i>D</i> _b	<i>r</i> ₃ max.	<i>r</i> ₄ max.	<i>e</i>	<i>Y</i> ₁	<i>Y</i> ₂	Inner ring	Outer ring
16150	16283	19.8	49.5	43.0	61.0	67.0	3.6	2.4	0.40	1.49	0.82	0.207	0.183

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952426594
Inside diameter	38.1 mm
Outside diameter	72.238 mm
Thickness	23.812 mm
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE