

Tapered roller bearing 2788R-2735X-JTEKT - 2788R-2735X-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/2788r-2735x-jtekt>

Single-row tapered roller bearings inch series Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
d	D	T	B	C	r ₁ max.	r ₁ min.	C _r	C ₁₀	Grease lub.	Oil lub.
38.100	73.025	23.812	25.664	19.050	3.6	0.8	74.1	92.2	5 400	7 200

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer to) Mass (kg)	
Inner ring	Outer ring	a	d _a	d _b	D _a	D _b	r _a max.	r _b max.	e	Y ₁	Y ₂	Inner ring	Outer ring
2788R	2735X	15.9	50.0	43.5	66.0	69.0	3.6	0.8	0.30	1.98	1.09	0.308	0.134

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952426600
Inside diameter	38.1 mm
Outside diameter	73.025 mm
Thickness	23.812 mm
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE