

Tapered roller bearing 25572-25520-JTEKT - 25572-25520-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/25572-25520-jtekt>

Single-row tapered roller bearings inch series **Koyo**



Boundary dimensions (mm)								Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
d	D	T	B	C	r ₁	r ₂	r ₃	C _r	C ₁₀	Grease lub.	Oil lub.
38.100	82.931	23.812	25.400	19.050	0.8	0.8		77.2	100	4 800	6 300

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer to)	
Inner ring	Outer ring	a	d _a	d _b	D _a	D _b	r _a max.	r _b max.	e	Y ₁	Y ₂	Inner ring	Outer ring
25572	25520	17.5	46.0	46.0	74.0	77.0	0.8	0.8	0.33	1.79	0.99	0.437	0.203

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952426662
Inside diameter	38.1 mm
Outside diameter	82.931 mm
Thickness	23.812 mm
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE