


Tapered roller bearing 2789R-2735X-JTEKT - 2789R-2735X-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/2789r-2735x-jtekt>

Single-row tapered roller bearings inch series Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r</i> _a	<i>r</i> _b	<i>C</i> _r	<i>C</i> ₁₀	Grease lub.	Oil lub.
39.688	73.025	23.812	25.664	19.050	3.6	0.8	74.1	92.2	5 400	7 200

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer) Mass (kg)	
Inner ring	Outer ring	<i>a</i>	<i>d</i> _a	<i>d</i> _b	<i>D</i> _a	<i>D</i> _b	<i>r</i> _a max.	<i>r</i> _b max.	<i>e</i>	<i>Y</i> ₁	<i>Y</i> ₂	Inner ring	Outer ring
2789R	2735X	15.9	52.0	45.0	66.0	69.0	3.6	0.8	0.30	1.98	1.09	0.288	0.134

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952426709
Inside diameter	39.688 mm
Outside diameter	73.025 mm
Thickness	23.812 mm
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE