


# Tapered roller bearing 420-414-JTEKT - 420-414-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/420-414-jtekt>

Single-row tapered roller bearings ————— **Koyo**  
inch series



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r<sub>a</sub></i> max.	<i>r<sub>b</sub></i> max.	<i>C<sub>r</sub></i>	<i>C<sub>10</sub></i>	Grease lub.	Oil lub.
40.000	88.501	26.988	29.083	22.225	3.6	1.6	98.2	112	4 900	6 500

Bearing No.		Load center (mm)	Mounting dimensions (mm)					Constant	Axial load factors		(Refer) Mass (kg)		
Inner ring	Outer ring	<i>a</i>	<i>d<sub>a</sub></i>	<i>d<sub>b</sub></i>	<i>D<sub>a</sub></i>	<i>D<sub>b</sub></i>	<i>r<sub>a</sub></i> max.	<i>r<sub>b</sub></i> max.	<i>e</i>	<i>Y<sub>1</sub></i>	<i>Y<sub>2</sub></i>	Inner ring	Outer ring
420	414	16.9	52.0	46.0	77.0	80.0	3.6	1.6	0.26	2.28	1.25	0.465	0.325

## PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952426792
Inside diameter	40 mm
Inside diameter	1.575" inch
Outside diameter	88.501 mm
Outside diameter	3.484" inch
Thickness	26.988 mm
Thickness	1 1/16" inch
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE