

Tapered roller bearing 543-532X-JTEKT - 543-532X-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/543-532x-jtekt>

Single-row tapered roller bearings Koyo
inch series



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
d	D	T	B	C	r ₁ max.	r ₁ min.	C _r	C ₁₀	Grease lub.	Oil lub.
40.000	107.950	36.512	36.967	22.675	3.6	3.2	138	172	3 800	5 100

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer.) Mass (kg)	
Inner ring	Outer ring	a	d _a	d _b	D _a	D _b	r _a max.	r _b max.	e	Y ₁	Y ₂	Inner ring	Outer ring
543	532X	23.9	57.0	50.0	94.0	100.0	3.6	3.2	0.30	2.03	1.11	1.17	0.570

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952426808
Inside diameter	40 mm
Inside diameter	1.575" inch
Outside diameter	107.95 mm
Outside diameter	4 1/4" inch
Thickness	36.512 mm
Thickness	1 7/16" inch
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE