

## Tapered roller bearing 365A-362A-JTEKT - 365A-362A-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/365a-362a-jtekt>

Single-row tapered roller bearings  
Inch series Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	
d	D	T	B	C	r <sub>1</sub>	r <sub>2</sub>	C <sub>r</sub>	C <sub>10</sub>	Grease lub.	Oil lub.
41.275	88.900	20.638	22.225	18.513	3.6	1.2	74.3	87.3	4 400	5 800

  

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer to)	
Inner ring	Outer ring	a	d <sub>a</sub>	d <sub>b</sub>	D <sub>a</sub>	D <sub>b</sub>	r <sub>a</sub> max.	r <sub>b</sub> max.	e	Y <sub>1</sub>	Y <sub>2</sub>	Inner ring	Outer ring
365A	362A	16.1	55.0	48.5	81.0	84.0	3.6	1.2	0.32	1.88	1.03	0.458	0.164

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952426877
Inside diameter	41.275 mm
Outside diameter	88.9 mm
Thickness	20.638 mm
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE