

Tapered roller bearing 12168-12303-JTEKT - 12168-12303-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/12168-12303-jtekt>

Single-row tapered roller bearings
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
d	D	T	B	C	r ₁ max.	r ₁ min.	C _r	C ₁₀	Grease lub.	Oil lub.
42.862	76.992	17.463	17.145	11.908	1.6	1.6	48.4	82.2	5 000	6 600

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer to Mass (kg))	
Inner ring	Outer ring	a	d _a	d _b	D _a	D _b	r _a max.	r _b max.	e	Y ₁	Y ₂	Inner ring	Outer ring
12168	12303	17.5	51.0	48.5	68.0	73.0	1.6	1.6	0.51	1.19	0.65	0.220	0.097

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952426983
Inside diameter	42.862 mm
Outside diameter	76.992 mm
Thickness	17.463 mm
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE