


## Tapered roller bearing 49576-49520-JTEKT - 49576-49520-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/49576-49520-jtekt>

Single-row tapered roller bearings  
inch series Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	
d	D	T	B	C	r <sub>1</sub>	r <sub>2</sub>	C <sub>r</sub>	C <sub>10</sub>	Grease lub.	Oil lub.
44.450	98.425	30.162	31.760	25.400	0.8	3.2	114	143	3 900	5 200

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		Mass (kg)	
Inner ring	Outer ring	a	d <sub>a</sub>	d <sub>b</sub>	D <sub>a</sub>	D <sub>b</sub>	r <sub>a</sub> max.	r <sub>b</sub> max.	e	Y <sub>1</sub>	Y <sub>2</sub>	Inner ring	Outer ring
49576	49520	24.1	55.0	54.0	88.0	96.0	0.8	3.2	0.40	1.50	0.82	0.856	0.384

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952427164
Inside diameter	44.45 mm
Outside diameter	98.425 mm
Thickness	30.162 mm
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE