


Tapered roller bearing 535-532A-JTEKT - 535-532A-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/535-532a-jtekt>

Single-row tapered roller bearings — Koyo
inch series



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r_a</i>	<i>r_b</i>	<i>C_r</i>	<i>C₁₀</i>	Grease lub.	Oil lub.
44.450	111.125	38.100	36.967	32.162	3.6	3.2	138	172	3 800	5 100

Bearing No.		Load center (mm)	Mounting dimensions (mm)					Con-stant	Axial load factors		(Refer.) Mass (kg)		
Inner ring	Outer ring	<i>a</i>	<i>d_a</i>	<i>d_b</i>	<i>D_a</i>	<i>D_b</i>	<i>r_a</i> max.	<i>r_b</i> max.	<i>e</i>	<i>Y₁</i>	<i>Y₂</i>	Inner ring	Outer ring
535	532A	23.9	60.0	54.0	95.0	100.0	3.6	3.2	0.30	2.03	1.11	1.09	0.746

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952427188
Inside diameter	44.45 mm
Inside diameter	1 3/4" inch
Outside diameter	111.125 mm
Outside diameter	4 3/8" inch
Thickness	38.1 mm
Thickness	1 1/2" inch
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE