

## Tapered roller bearing 358-354A-JTEKT - 358-354A-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/358-354a-jtekt>

Single-row tapered roller bearings inch series Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	
d	D	T	B	C	r <sub>1</sub>	r <sub>2</sub>	C <sub>r</sub>	C <sub>10</sub>	Grease lub.	Oil lub.
45.000	85.000	20.638	21.692	17.462	1.6	1.2	71.8	81.7	4 600	6 200

  

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer to) Mass (kg)	
Inner ring	Outer ring	a	d <sub>a</sub>	d <sub>b</sub>	D <sub>a</sub>	D <sub>b</sub>	r <sub>a</sub> max.	r <sub>b</sub> max.	e	Y <sub>1</sub>	Y <sub>2</sub>	Inner ring	Outer ring
358	354A	15.5	52.5	50.0	77.0	80.0	1.6	1.2	0.31	1.96	1.08	0.338	0.162

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952427218
Inside diameter	45 mm
Outside diameter	85 mm
Thickness	20.638 mm
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE