

Tapered roller bearing HM804848-HM804810-JTEKT - HM804848-HM804810-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/hm804848-hm804810-jtekt>

Single-row tapered roller bearings — Koyo
inch series



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r</i> _a	<i>r</i> _b	<i>C</i> _r	<i>C</i> ₁₀	Grease lub.	Oil lub.
48.412	95.250	30.162	29.370	22.020	2.4	3.2	104	140	3 300	4 400

Bearing No.		Load center (mm)	Mounting dimensions (mm)					Constant	Axial load factors		(Refer to)		
Inner ring	Outer ring	<i>a</i>	<i>d</i> _a	<i>d</i> _b	<i>D</i> _a	<i>D</i> _b	<i>r</i> _a max.	<i>r</i> _b max.	<i>e</i>	<i>Y</i> ₁	<i>Y</i> ₂	Inner ring	Outer ring
HM804848	HM804810	26.5	63.0	57.5	81.0	91.0	2.4	3.2	0.55	1.10	0.60	0.606	0.351

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952427416
Inside diameter	48.412 mm
Outside diameter	95.25 mm
Thickness	30.162 mm
Weight	944 g
Packaging	-

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE