

## Tapered roller bearing 365-362A-JTEKT - 365-362A-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/365-362a-jtekt>

Single-row tapered roller bearings ————— **Koyo**  
inch series



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	
$d$	$D$	$T$	$B$	$C$	$r_a$ max.	$r_b$ min.	$C_r$	$C_{10}$	Grease lub.	Oil lub.
50.000	88.900	20.638	22.225	16.913	2.0	1.2	74.3	87.3	4 400	5 800

  

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer to) Mass (kg)	
Inner ring	Outer ring	$a$	$d_a$	$d_b$	$D_a$	$D_b$	$r_a$ max.	$r_b$ max.	$e$	$Y_1$	$Y_2$	Inner ring	Outer ring
365	362A	16.1	58.0	55.0	81.0	84.0	2.0	1.2	0.32	1.88	1.03	0.346	0.164

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952427584
Inside diameter	50 mm
Outside diameter	88.9 mm
Thickness	20.638 mm
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE