


Tapered roller bearing 366-362A-JTEKT - 366-362A-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/366-362a-jtekt>

Single-row tapered roller bearings ————— **Koyo**
inch series



| Boundary dimensions (mm) | | | | | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | |
|--------------------------|--------|--------|--------|--------|---------------|---------------|-------------------------|----------|--------------------------------------|----------|
| d | D | T | B | C | r_a max. | r_b min. | C_r | C_{10} | Grease lub. | Oil lub. |
| 50.000 | 88.900 | 20.638 | 22.225 | 16.913 | 2.4 | 1.2 | 74.3 | 87.3 | 4 400 | 5 800 |

| Bearing No. | | Load center (mm) | Mounting dimensions (mm) | | | | | | Constant | Axial load factors | | (Refer to) Mass (kg) | |
|-------------|------------|------------------|--------------------------|-------|-------|-------|---------------|---------------|----------|--------------------|-------|----------------------|------------|
| Inner ring | Outer ring | a | d_a | d_b | D_a | D_b | r_a max. | r_b max. | e | Y_1 | Y_2 | Inner ring | Outer ring |
| 366 | 362A | 16.1 | 59.0 | 55.0 | 81.0 | 84.0 | 2.4 | 1.2 | 0.32 | 1.88 | 1.03 | 0.351 | 0.166 |

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | JTEKT |
| N° Ean13 | 3663952427591 |
| Inside diameter | 50 mm |
| Outside diameter | 88.9 mm |
| Thickness | 20.638 mm |
| Packaging | 1 |

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE