

Tapered roller bearing L305649R-L305610-JTEKT - L305649R-L305610-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/l305649r-l305610-jtekt>

Single-row tapered roller bearings
inch series Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
d	D	T	B	C	r ₁	r ₂	C _r	C ₁₀	Grease lub.	Oil lub.
50.800	80.962	18.258	18.258	14.288	1.6	1.6	54.0	81.1	4 600	6 100

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer to)	
Inner ring	Outer ring	a	d _a	d _b	D _a	D _b	r _a max.	r _b max.	e	Y ₁	Y ₂	Inner ring	Outer ring
L305649R	L305610	16.0	58.0	56.0	73.0	77.0	1.6	1.6	0.35	1.69	0.93	0.228	0.119

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952427638
Inside diameter	50.8 mm
Outside diameter	80.962 mm
Thickness	18.258 mm
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE