

## Tapered roller bearing 18790-18724-JTEKT - 18790-18724-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/18790-18724-jtekt>

Single-row tapered roller bearings inch series **Koyo**



Boundary dimensions (mm)										Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	
d	D	T	B	C	r <sub>1</sub>	r <sub>2</sub>	r <sub>3</sub>	r <sub>4</sub>	r <sub>5</sub>	C <sub>r</sub>	C <sub>10</sub>	Grease lub.	Oil lub.
50.800	88.900	17.462	17.462	12.485	3.6	1.2				49.7	65.5	4 400	5 900

  

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer to)	
Inner ring	Outer ring	a	d <sub>a</sub>	d <sub>b</sub>	D <sub>a</sub>	D <sub>b</sub>	r <sub>a</sub> max.	r <sub>b</sub> max.	e	Y <sub>1</sub>	Y <sub>2</sub>	Inner ring	Outer ring
18790	18724	17.4	62.0	56.0	78.0	82.0	3.6	1.2	0.41	1.48	0.61	0.226	0.190

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952427652
Inside diameter	50.8 mm
Outside diameter	88.9 mm
Thickness	17.462 mm
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE