

## Tapered roller bearing 619-612-JTEKT - 619-612-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/619-612-jtekt>

Single-row tapered roller bearings  
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	
$d$	$D$	$T$	$B$	$C$	$r_a$ max.	$r_b$ max.	$C_r$	$C_{10}$	Grease lub.	Oil lub.
50.800	120.650	41.275	41.275	31.750	3.6	3.2	174	217	3 500	4 600

  

Bearing No.		Load center (mm)	Mounting dimensions (mm)					Constant	Axial load factors		Mass (kg)		
Inner ring	Outer ring	$a$	$d_a$	$d_b$	$D_a$	$D_b$	$r_a$ max.	$r_b$ max.	$e$	$Y_1$	$Y_2$	Inner ring	Outer ring
619	612	27.3	67.0	61.0	105.0	110.0	3.6	3.2	0.31	1.91	1.05	1.44	0.853

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952427805
Inside diameter	50.8 mm
Outside diameter	120.65 mm
Thickness	41.275 mm
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE