

## Tapered roller bearing 66584-66520-JTEKT - 66584-66520-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/66584-66520-jtekt>

Single-row tapered roller bearings  
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)			Limiting speeds (min <sup>-1</sup> )	
d	D	T	B	C	r <sub>1</sub> max.	r <sub>1</sub> min.	C <sub>r</sub>	C <sub>10</sub>	Grease lub.	Oil lub.	
53.975	122.238	33.338	31.750	22.812	3.6	3.2	128	153	3 300	4 300	

  

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer) Mass (kg)	
Inner ring	Outer ring	a	d <sub>a</sub>	d <sub>b</sub>	D <sub>a</sub>	D <sub>b</sub>	r <sub>a</sub> max.	r <sub>b</sub> max.	e	Y <sub>1</sub>	Y <sub>2</sub>	Inner ring	Outer ring
66584	66520	35.4	75.0	68.0	105.0	116.0	3.6	3.2	0.67	0.90	0.50	1.25	0.551

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952427928
Inside diameter	53.975 mm
Inside diameter	2 1/8" inch
Outside diameter	122.238 mm
Outside diameter	4 13/16" inch
Thickness	33.338 mm
Thickness	1 5/16" inch
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE