

Tapered roller bearing 6381-6320-JTEKT - 6381-6320-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/6381-6320-jtekt>

Single-row tapered roller bearings
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
d	D	T	B	C	d _a	d _b	C _r	C ₁₀	Grease lub.	Oil lub.
54.991	135.755	53.975	56.007	44.450	3.6	3.2	286	357	3 000	4 000

Bearing No.		Load center (mm)	Mounting dimensions (mm)					Constant	Axial load factors		(Refer to) Mass (kg)		
Inner ring	Outer ring	a	d _a	d _b	D _a	D _b	r _a max.	r _b max.	e	Y ₁	Y ₂	Inner ring	Outer ring
6381	6320	34.8	76.0	70.0	117.0	126.0	3.6	3.2	0.32	1.85	1.02	2.75	1.37

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952427973
Inside diameter	54.991 mm
Outside diameter	135.755 mm
Thickness	53.975 mm
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE