

## Tapered roller bearing 45291-45221-JTEKT - 45291-45221-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/45291-45221-jtekt>

Single-row tapered roller bearings  
inch series

Koyo



Boundary dimensions (mm)										Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	
d	D	T	B	C	r <sub>1</sub>	r <sub>2</sub>	r <sub>3</sub>	r <sub>4</sub>	r <sub>5</sub>	C <sub>r</sub>	C <sub>10</sub>	Grease lub.	Oil lub.
57.150	104.775	30.162	30.958	22.812	6.4	0.8				126	165	3 700	4 900

  

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer) Mass (kg)	
Inner ring	Outer ring	a	d <sub>a</sub>	d <sub>b</sub>	D <sub>a</sub>	D <sub>b</sub>	r <sub>a</sub> max.	r <sub>b</sub> max.	e	Y <sub>1</sub>	Y <sub>2</sub>	Inner ring	Outer ring
45291	45221	22.2	76.0	65.0	95.0	99.0	6.4	0.8	0.33	1.80	0.99	0.742	0.350

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952428178
Inside diameter	57.15 mm
Outside diameter	104.775 mm
Thickness	30.162 mm
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE