

Tapered roller bearing 623-612-JTEKT - 623-612-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/623-612-jtekt>

Single-row tapered roller bearings
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)			Limiting speeds (min ⁻¹)	
d	D	T	B	C	r_1 max.	r_2 max.	C_r	C_{10}	Grease lub. Oil lub.		
57.150	120.650	41.275	41.275	31.750	3.6	3.2	174	217	3 500	4 600	

Bearing No.		Load center (mm)	Mounting dimensions (mm)					Constant	Axial load factors		(Refer to Mass (kg))		
Inner ring	Outer ring	a	d_a	d_b	D_a	D_b	r_a max.	r_b max.	e	Y_1	Y_2	Inner ring	Outer ring
623	612	27.3	72.0	66.0	105.0	110.0	3.6	3.2	0.31	1.91	1.05	1.27	0.853

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250164552
Inside diameter	57.15 mm
Outside diameter	120.65 mm
Thickness	41.65 mm
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE