

Tapered roller bearing 66589-66520-JTEKT - 66589-66520-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/66589-66520-jtekt>

Single-row tapered roller bearings
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)			Limiting speeds (min ⁻¹)	
d	D	T	B	C	r ₁	r ₂	C _r	C ₁₀	Grease lub. Oil lub.		
59.972	122.238	33.338	31.750	22.812	0.8	3.2	128	153	3 300	4 300	

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer to)	
Inner ring	Outer ring	a	d _a	d _b	D _a	D _b	r _a max.	r _b max.	e	Y ₁	Y ₂	Inner ring	Outer ring
66589	66520	35.4	74.0	73.0	105.0	116.0	0.8	3.2	0.67	0.90	0.50	1.11	0.551

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952428246
Inside diameter	59.972 mm
Outside diameter	122.238 mm
Thickness	33.338 mm
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE