

# Tapered roller bearing

## JLM508748-JLM508710-JTEKT - JLM508748-JLM508710-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/jlm508748-jlm508710-jtekt>

Single-row tapered roller bearings  
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	
$d$	$D$	$T$	$B$	$C$	$r_a$ max.	$r_b$ min.	$C_r$	$C_{10}$	Grease lub.	Oil lub.
60.000	95.000	24.000	24.000	19.000	5.0	2.5	86.1	125	3 900	5 200

  

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer) Mass (kg)	
Inner ring	Outer ring	$a$	$d_a$	$d_b$	$D_a$	$D_b$	$r_a$ max.	$r_b$ max.	$e$	$Y_1$	$Y_2$	Inner ring	Outer ring
JLM508748	JLM508710	21.2	75.0	66.0	85.0	91.0	5.0	2.5	0.40	1.49	0.82	0.402	0.196

## PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952428253
Inside diameter	60 mm
Outside diameter	95 mm
Thickness	24 mm
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE