


## Tapered roller bearing 39590-39521-JTEKT - 39590-39521-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/39590-39521-jtekt>

Single-row tapered roller bearings inch series Koyo



| Boundary dimensions (mm) |          |          |          |          |                              |                              | Basic load ratings (kN) |                       |                      | Limiting speeds (min <sup>-1</sup> ) |  |
|--------------------------|----------|----------|----------|----------|------------------------------|------------------------------|-------------------------|-----------------------|----------------------|--------------------------------------|--|
| <i>d</i>                 | <i>D</i> | <i>T</i> | <i>B</i> | <i>C</i> | <i>r<sub>a</sub></i><br>max. | <i>r<sub>b</sub></i><br>max. | <i>C<sub>r</sub></i>    | <i>C<sub>10</sub></i> | Grease lub. Oil lub. |                                      |  |
| 66.675                   | 112.712  | 30.162   | 30.162   | 22.812   | 3.6                          | 0.8                          | 147                     | 207                   | 3 300                | 4 500                                |  |

| Bearing No. |            | Load center (mm) | Mounting dimensions (mm) |                      |                      |                      |                              |                              | Con-stant | Axial load factors   |                      | (Refer) Mass (kg) |            |
|-------------|------------|------------------|--------------------------|----------------------|----------------------|----------------------|------------------------------|------------------------------|-----------|----------------------|----------------------|-------------------|------------|
| Inner ring  | Outer ring | <i>a</i>         | <i>d<sub>a</sub></i>     | <i>d<sub>b</sub></i> | <i>D<sub>a</sub></i> | <i>D<sub>b</sub></i> | <i>r<sub>a</sub></i><br>max. | <i>r<sub>b</sub></i><br>max. | <i>e</i>  | <i>Y<sub>1</sub></i> | <i>Y<sub>2</sub></i> | Inner ring        | Outer ring |
| 39590       | 39521      | 23.3             | 80.0                     | 74.0                 | 103.0                | 107.0                | 3.6                          | 0.8                          | 0.34      | 1.77                 | 0.97                 | 0.832             | 0.360      |

### PRODUCT FEATURES

|                  |               |
|------------------|---------------|
| Brand            | JTEKT         |
| N° Ean13         | 3663952428611 |
| Inside diameter  | 66.675 mm     |
| Inside diameter  | 2 5/8" inch   |
| Outside diameter | 112.712 mm    |
| Outside diameter | 4 7/16" inch  |
| Thickness        | 30.162 mm     |
| Thickness        | 1 3/16" inch  |
| Packaging        | 1             |

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE