


Tapered roller bearing HM212049-HM212010-JTEKT - HM212049-HM212010-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/hm212049-hm212010-jtekt>

Single-row tapered roller bearings
inch series Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r_a</i> max.	<i>r_b</i> max.	<i>C_r</i>	<i>C₁₀</i>	Grease lub.	Oil lub.
66.675	122.238	38.100	38.364	22.718	3.6	1.6	191	249	3 200	4 300

Bearing No.		Load center (mm) <i>a</i>	Mounting dimensions (mm)						Constant <i>e</i>	Axial load factors		(Refer.) Mass (kg)	
Inner ring	Outer ring		<i>d_a</i>	<i>d_b</i>	<i>D_a</i>	<i>D_b</i>	<i>r_a</i> max.	<i>r_b</i> max.		<i>Y₁</i>	<i>Y₂</i>	Inner ring	Outer ring
HM212049	HM212010	27.3	82.0	75.5	110.0	116.0	3.6	1.6	0.34	1.78	0.98	1.26	0.596

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952428635
Inside diameter	66.675 mm
Inside diameter	2 5/8" inch
Outside diameter	122.238 mm
Outside diameter	4 13/16" inch
Thickness	38.1 mm
Thickness	1 1/2" inch
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE