


## Tapered roller bearing 6386-6320-JTEKT - 6386-6320-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/6386-6320-jtekt>

Single-row tapered roller bearings inch series Koyo



Boundary dimensions (mm)								Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r<sub>a</sub></i>	<i>r<sub>b</sub></i>	<i>r<sub>1</sub></i>	<i>C<sub>r</sub></i>	<i>C<sub>10</sub></i>	Grease lub.	Oil lub.
66.675	135.755	53.975	56.007	44.460	4.3	3.2		266	357	3 000	4 000

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer to)	
Inner ring	Outer ring	<i>a</i>	<i>d<sub>a</sub></i>	<i>d<sub>b</sub></i>	<i>D<sub>a</sub></i>	<i>D<sub>b</sub></i>	<i>r<sub>a</sub></i> max.	<i>r<sub>b</sub></i> max.	<i>e</i>	<i>Y<sub>1</sub></i>	<i>Y<sub>2</sub></i>	Inner ring	Outer ring
6386	6320	34.8	87.0	77.5	117.0	126.0	4.3	3.2	0.32	1.85	1.02	2.27	1.37

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952428666
Inside diameter	66.675 mm
Outside diameter	135.755 mm
Thickness	53.975 mm
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE