

Tapered roller bearing 6389-6320-JTEKT - 6389-6320-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/6389-6320-jtekt>

Single-row tapered roller bearings ————— **Koyo**
inch series

Boundary dimensions (mm)								Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
d	D	T	B	C	r ₁	r ₂	r ₃	C _r	C ₁₀	Grease lub.	Oil lub.
66.675	135.755	53.975	56.007	44.450	6.4	3.2		266	357	3 000	4 000

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer to)	
Inner ring	Outer ring	a	d _a	d _b	D _a	D _b	r _a max.	r _b max.	e	Y ₁	Y ₂	Inner ring	Outer ring
6389	6320	34.8	91.0	77.5	117.0	126.0	6.4	3.2	0.32	1.85	1.02	2.15	1.37

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952428673
Inside diameter	66.675 mm
Outside diameter	135.755 mm
Thickness	53.975 mm
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE