

Tapered roller bearing 744R-742-JTEKT - 744R-742-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/744r-742-jtekt>

Single-row tapered roller bearings
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
d	D	T	B	C	r ₁	r ₂	C _r	C ₁₀	Grease lub.	Oil lub.
73.025	150.089	44.450	46.672	38.612	3.6	3.2	264	368	2 500	3 400

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer) Mass (kg)	
Inner ring	Outer ring	a	d _a	d _b	D _a	D _b	r _a max.	r _b max.	e	Y ₁	Y ₂	Inner ring	Outer ring
744R	742	32.4	91.0	85.0	134.0	142.0	3.6	3.2	0.33	1.84	1.01	2.66	1.07

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952428987
Inside diameter	73.025 mm
Inside diameter	2 7/8" inch
Outside diameter	150.089 mm
Outside diameter	5.909" inch
Thickness	44.45 mm
Thickness	1 3/4" inch
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE