

# Tapered roller bearing 762-752-JTEKT - 762-752-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/762-752-jtekt>

Single-row tapered roller bearings  
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	
$d$	$D$	$T$	$B$	$C$	$r_a$ max.	$r_b$ max.	$C_r$	$C_{10}$	Grease lub.	Oil lub.
73.025	161.925	47.625	48.260	38.100	3.6	3.2	273	391	2 400	3 200

  

Bearing No.		Load center (mm) $a$	Mounting dimensions (mm)						Constant $e$	Axial load factors		(Refer to) Mass (kg)	
Inner ring	Outer ring		$d_a$	$d_b$	$D_a$	$D_b$	$r_a$ max.	$r_b$ max.		$Y_1$	$Y_2$	Inner ring	Outer ring
762	752	35.5	92.0	97.0	144.0	150.0	3.6	3.2	0.34	1.76	0.97	3.18	1.61

## PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952428994
Inside diameter	73.025 mm
Outside diameter	161.925 mm
Thickness	47.625 mm
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE