

Tapered roller bearing 29688-29620-JTEKT - 29688-29620-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/29688-29620-jtekt>

Single-row tapered roller bearings
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)			Limiting speeds (min ⁻¹)	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r</i> ₁ max.	<i>r</i> ₁ min.	<i>C</i> _r	<i>C</i> _{10v}	Grease lub.	Oil lub.	
73.817	112.712	25.400	25.400	19.050	1.6	3.2	97.0	155	3 200	4 300	

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Con-stant	Axial load factors		(Refer) Mass (kg)	
Inner ring	Outer ring	<i>a</i>	<i>d</i> _a	<i>d</i> _b	<i>D</i> _a	<i>D</i> _b	<i>r</i> _a max.	<i>r</i> _b max.	<i>e</i>	<i>Y</i> ₁	<i>Y</i> ₂	Inner ring	Outer ring
29688	29620	26.2	83.0	81.0	101.0	109.0	1.6	3.2	0.49	1.23	0.68	0.588	0.270

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952429007
Inside diameter	73.817 mm
Outside diameter	112.712 mm
Thickness	25.4 mm
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE