


Tapered roller bearing 568-563-JTEKT - 568-563-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/568-563-jtekt>

Single-row tapered roller bearings
inch series Koyo



Boundary dimensions (mm)							Basic load ratings (kN)			Limiting speeds (min ⁻¹)	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r</i> _{max.}	<i>r</i> _{min.}	<i>C</i> _r	<i>C</i> ₁₀	Grease lub. Oil lub.		
73.817	127.000	36.512	36.170	28.575	0.8	3.2	156	226	3 000	4 000	

Bearing No.		Load center (mm) <i>a</i>	Mounting dimensions (mm)						Constant <i>e</i>	Axial load factors		(Refer.) Mass (kg)	
Inner ring	Outer ring		<i>d</i> _a	<i>d</i> _b	<i>D</i> _a	<i>D</i> _b	<i>r</i> _a max.	<i>r</i> _b max.		<i>Y</i> ₁	<i>Y</i> ₂	Inner ring	Outer ring
568	563	28.6	83.0	82.0	112.0	120.0	0.8	3.2	0.36	1.65	0.91	1.12	0.648

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952429014
Inside diameter	73.817 mm
Outside diameter	127 mm
Thickness	36.512 mm
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE