

## Tapered roller bearing 575SR-572-JTEKT - 575SR-572-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/575sr-572-jtekt>

Single-row tapered roller bearings  
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	
$d$	$D$	$T$	$B$	$C$	$r_a$ max.	$r_b$ max.	$C_r$	$C_{10}$	Grease lub.	Oil lub.
76.200	139.992	36.512	36.088	28.575	6.7	3.2	175	262	2 700	3 600

  

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer to Mass (kg))	
Inner ring	Outer ring	$a$	$d_a$	$d_b$	$D_a$	$D_b$	$r_a$ max.	$r_b$ max.	$e$	$Y_1$	$Y_2$	Inner ring	Outer ring
575SR	572	31.0	99.0	86.0	125.0	133.0	6.7	3.2	0.40	1.49	0.82	1.61	0.779

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952429144
Inside diameter	76.2 mm
Outside diameter	139.992 mm
Thickness	36.512 mm
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE